

#### ..... 21/06/2022

Date of	compilation: 21/06/2022	Version: 1	
SECT	TION 1: IDENTIFICATIO	N OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING	
1.1	Product identifier:	0RS110P-1L	
	Other means of identified	cation:	
	UFI:	3CH6-W06T-F00A-XPMJ	
1.2	Relevant identified uses	s of the substance or mixture and uses advised against:	
	Relevant uses: Anticorrosio	n primer. For professional users only.	
	Uses advised against: All us	ses not specified in this section or in section 7.3	

#### 1.3 Details of the supplier of the safety data sheet:

Inter Cars S.A. ul. Powsińska 64 02-903 Warszawa - Polska kontakt@intercars.com www.intercars.com

#### 1.4 Emergency telephone number:

#### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture:

#### CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412 Asp. Tox. 1: Aspiration hazard, Category 1, H304 Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Liq. 3: Flammable liquids, Category 3, H226 Skin Irrit. 2: Skin irritation, Category 2, H315 STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373

#### 2.2 Label elements:

#### CLP Regulation (EC) No 1272/2008:

Dange



#### Hazard statements:

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H373 May cause damage to organs through prolonged or repeated exposure (Oral).
- H412 Harmful to aquatic life with long lasting effects.

#### **Precautionary statements:**

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/protective footwear.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsina.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

#### Supplementary information:

EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

## Substances that contribute to the classification

**Xylene** 

UFI: 3CH6-W06T-F00A-XPMJ



# Date of compilation: 21/06/2022 Version: 1

# SECTION 2: HAZARDS IDENTIFICATION (continued)

#### 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria Endocrine-disrupting properties: The product fails to meet the criteria.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substance:

Non-applicable

## 3.2 Mixture:

### Chemical description: Mixture composed of chemical products

#### Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification	Chemical name/Classification			
CAS: EC:	1330-20-7	Xylene <sup>(1)</sup>	Self-classified		
Index:	215-535-7 601-022-00-9 01-2119488216-32- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	10 - <25 %	
CAS: EC:	7779-90-0 231-944-3	trizinc bis(orthophos	phate) <sup>(1)</sup> Self-classified		
Index:	Non-applicable 01-2119485044-40- XXXX	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning	10 - <25 %	
CAS:	108-65-6 203-603-9	2-methoxy-1-methyl	ethyl acetate <sup>(1)</sup> Self-classified		
	203-603-9 607-195-00-7 01-2119475791-29- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	2,5 - <10 %	
	123-86-4	N-butyl acetate <sup>(1)</sup>	ATP CLP00		
	204-658-1 607-025-00-1 : 01-2119485493-29- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	2,5 - <10 %	
CAS:	108-65-6 203-603-9 607-195-00-7 : 01-2119475791-29- XXXX	2-methoxy-1-methyl	ethyl acetate <sup>(2)</sup> ATP ATP01		
		Regulation 1272/2008	Flam. Liq. 3: H226 - Warning	1 - <2,5 %	
CAS:	100-41-4	Ethylbenzene <sup>(2)</sup>	ATP ATP06		
	202-849-4 601-023-00-4 : 01-2119489370-35- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	<1 %	
CAS: EC:	1314-13-2	zinc oxide <sup>(1)</sup>	ATP CLP00		
Index:	215-222-5 030-013-00-7 01-2119463881-32- XXXX	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning	<1 %	
CAS:	141-32-2	n-butyl acrylate <sup>(2)</sup>	Self-classified		
	205-480-7 607-062-00-3 01-2119453155-43- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; Skin Sens. 1B: H317; STOT SE 3: H335 - Warning	<1 %	

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878 <sup>(2)</sup> Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

#### Other information:

Identification	Specific concentration limit
CAS: 7779-90-0 EC: 231-944-3	% (w/w) >=50: Aquatic Acute 1 - H400 % (w/w) >=97: Aquatic Chronic 2 - H411 97<= % (w/w) <97: Aquatic Chronic 3 - H412 25<= % (w/w) <97: Aquatic Chronic 1 - H410



# Date of compilation: 21/06/2022 Version: 1

# SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

# By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

#### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

#### By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media:

#### Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2).

### Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

# 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

#### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:



#### Date of compilation: 21/06/2022 Version: 1

# SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

# For emergency responders:

See section 8.

### 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

# 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13.

# SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

# 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

	-
Minimum Temp.:	5 °C
Maximum Temp.:	25 °C
Maximum time:	24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

# 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION



Date of compilation: 21/06/2022 Version: 1

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

# 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Iden	tification	Occ	upational exposu	ure limits
Xylene		IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
CAS: 1330-20-7 EC: 215-535-7		IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate		IOELV (8h)	50 ppm	275 mg/m <sup>3</sup>
CAS: 108-65-6 EC: 203-603-9		IOELV (STEL)	100 ppm	550 mg/m <sup>3</sup>
N-butyl acetate		IOELV (8h)	50 ppm	241 mg/m <sup>3</sup>
CAS: 123-86-4 EC: 204-658-1		IOELV (STEL)	150 ppm	723 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate		IOELV (8h)	50 ppm	275 mg/m <sup>3</sup>
CAS: 108-65-6 EC: 203-603-9		IOELV (STEL)	100 ppm	550 mg/m <sup>3</sup>
Ethylbenzene		IOELV (8h)	100 ppm	442 mg/m <sup>3</sup>
CAS: 100-41-4 EC: 202-849-4		IOELV (STEL)	200 ppm	884 mg/m <sup>3</sup>
n-butyl acrylate		IOELV (8h)	2 ppm	11 mg/m <sup>3</sup>
CAS: 141-32-2 EC: 205-480-7		IOELV (STEL)	10 ppm	53 mg/m <sup>3</sup>

## DNEL (Workers):

		Short	Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local	
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable	
EC: 215-535-7	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	
trizinc bis(orthophosphate)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 7779-90-0	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable	
EC: 231-944-3	Inhalation	Non-applicable	Non-applicable	5 mg/m <sup>3</sup>	Non-applicable	
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable	
EC: 203-603-9	Inhalation	Non-applicable	550 mg/m <sup>3</sup>	275 mg/m <sup>3</sup>	Non-applicable	
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 123-86-4	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable	
EC: 204-658-1	Inhalation	600 mg/m <sup>3</sup>	600 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable	
EC: 203-603-9	Inhalation	Non-applicable	550 mg/m <sup>3</sup>	275 mg/m <sup>3</sup>	Non-applicable	
Ethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable	
EC: 202-849-4	Inhalation	Non-applicable	293 mg/m <sup>3</sup>	77 mg/m <sup>3</sup>	Non-applicable	
zinc oxide	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 1314-13-2	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable	
EC: 215-222-5	Inhalation	Non-applicable	Non-applicable	5 mg/m <sup>3</sup>	0,5 mg/m <sup>3</sup>	
n-butyl acrylate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 141-32-2	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
EC: 205-480-7	Inhalation	Non-applicable	Non-applicable	Non-applicable	11 mg/m <sup>3</sup>	

#### **DNEL (General population):**

	Short exposu		xposure	Long ex	kposure
Identification		Systemic	Local	Systemic	Local
Xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m³	65,3 mg/m <sup>3</sup>



# Date of compilation: 21/06/2022 Version: 1

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local	
trizinc bis(orthophosphate)	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable	
CAS: 7779-90-0	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable	
EC: 231-944-3	Inhalation	Non-applicable	Non-applicable	2,5 mg/m <sup>3</sup>	Non-applicable	
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable	
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable	
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m <sup>3</sup>	33 mg/m <sup>3</sup>	
N-butyl acetate	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable	
CAS: 123-86-4	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable	
EC: 204-658-1	Inhalation	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	35,7 mg/m <sup>3</sup>	35,7 mg/m <sup>3</sup>	
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable	
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable	
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m <sup>3</sup>	33 mg/m <sup>3</sup>	
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable	
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m <sup>3</sup>	Non-applicable	
zinc oxide	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable	
CAS: 1314-13-2	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable	
EC: 215-222-5	Inhalation	Non-applicable	Non-applicable	2,5 mg/m <sup>3</sup>	Non-applicable	

### PNEC:

Identification				
Xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
trizinc bis(orthophosphate)	STP	0,1 mg/L	Fresh water	0,0206 mg/L
CAS: 7779-90-0	Soil	35,6 mg/kg	Marine water	0,0061 mg/L
EC: 231-944-3	Intermittent	Non-applicable	Sediment (Fresh water)	117,8 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	56,5 mg/kg
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0,635 mg/L
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water	0,064 mg/L
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
N-butyl acetate	STP	35,6 mg/L	Fresh water	0,18 mg/L
CAS: 123-86-4	Soil	0,09 mg/kg	Marine water	0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0,635 mg/L
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water	0,064 mg/L
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg
zinc oxide	STP	0,1 mg/L	Fresh water	0,0206 mg/L
CAS: 1314-13-2	Soil	35,6 mg/kg	Marine water	0,0061 mg/L
EC: 215-222-5	Intermittent	Non-applicable	Sediment (Fresh water)	117,8 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	56,5 mg/kg

#### Date of compilation: 21/06/2022 Version: 1

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification					
n-butyl acrylate	STP	3,5 mg/L	Fresh water	0,003 mg/L	
CAS: 141-32-2	Soil	1 mg/kg	Marine water	0 mg/L	
EC: 205-480-7	Intermittent	0,011 mg/L	Sediment (Fresh water)	0,034 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,003 mg/kg	

#### 8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

#### B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory han protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)		EN 420:2004+A1:2010	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

#### D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Antistatic and fireproof protective clothing		EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
Mandatory foot protection	Safety footwear with antistatic and heat resistant properties		EN ISO 13287:2013 EN ISO 20345:2011	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
+	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	<b>+</b>	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

### **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D



	compilation: 21/06/2022 Version: 1	
SECT	TION 9: PHYSICAL AND CHEMICAL PROPERTIE	S
0.1	Information on basic physical and chemical pro	operties:
	Appearance:	
	Physical state at 20 °C:	Liquid
	Appearance:	Dense
	Colour:	Black
	Odour:	Characteristic
	Odour threshold:	Non-applicable *
	Volatility:	
	Boiling point at atmospheric pressure:	137 °C
	Vapour pressure at 20 °C:	773 Pa
	Vapour pressure at 50 °C:	4130,43 Pa (4,13 kPa)
	Evaporation rate at 20 °C:	Non-applicable *
	Product description:	
	Density at 20 °C:	1635 - 1705 kg/m³
	Relative density at 20 °C:	1,635 - 1,705
	Dynamic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 40 °C:	<20,5 mm²/s
	Concentration:	Non-applicable *
	pH:	Non-applicable *
	Vapour density at 20 °C:	Non-applicable *
	Partition coefficient n-octanol/water 20 °C:	Non-applicable *
	Solubility in water at 20 °C:	Non-applicable *
	Solubility properties:	Non-applicable *
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Flammability:	
	Flash Point:	30 °C
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	292 °C
	Lower flammability limit:	Not available
	Upper flammability limit:	Not available
	Particle characteristics:	
	Median equivalent diameter:	Non-applicable
).2	Other information:	
	Information with regard to physical hazard clas	sses:
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Corrosive to metals:	Non-applicable *
	Heat of combustion:	Non-applicable *
	Aerosols-total percentage (by mass) of flammable	Non-applicable *
	components:	
	Other safety characteristics:	
	Surface tension at 20 °C:	Non-applicable *

- CONTINUED ON NEXT PAGE -



### Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation

# **0RS110P-1L**

#### Date of compilation: 21/06/2022 Version: 1

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Refraction index:

Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

# SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

#### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

	Sunlight	Humidity
Not applicable Not applicable Risk of combustion	Avoid direct impact	Not applicable

#### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

# SECTION 11: TOXICOLOGICAL INFORMATION


#### **11.1** Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
  - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
  - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation



# **ORS110P-1L**

# Date of compilation: 21/06/2022 Version: 1

# SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
- IARC: Xylene (3); Ethylbenzene (2B); n-butyl acrylate (3); Titanium dioxide (2B)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

#### Other information:

Non-applicable

#### Specific toxicology information on the substances:

Identification	A	cute toxicity	Genus
N-butyl acetate	LD50 oral	12789 mg/kg	Rat
CAS: 123-86-4	LD50 dermal	14112 mg/kg	Rabbit
EC: 204-658-1	LC50 inhalation	23,4 mg/L (4 h)	Rat
Xylene	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg	Rat
EC: 215-535-7	LC50 inhalation	11 mg/L (ATEi)	
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	5100 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	>5000 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat
Ethylbenzene	LD50 oral	3500 mg/kg	Rat
CAS: 100-41-4	LD50 dermal	15354 mg/kg	Rabbit
EC: 202-849-4	LC50 inhalation	17,2 mg/L (4 h)	Rat
zinc oxide	LD50 oral	7950 mg/kg	Mouse
CAS: 1314-13-2	LD50 dermal	Non-applicable	
EC: 215-222-5	LC50 inhalation	Non-applicable	
n-butyl acrylate	LD50 oral	4000 mg/kg	
CAS: 141-32-2	LD50 dermal	Non-applicable	
EC: 205-480-7	LC50 inhalation	Non-applicable	

# **11.2** Information on other hazards:

### **Endocrine disrupting properties**

Endocrine-disrupting properties: The product fails to meet the criteria.



# Date of compilation: 21/06/2022 Version: 1

# SECTION 11: TOXICOLOGICAL INFORMATION (continued)

# **Other information**

Non-applicable

# SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

# 12.1 Toxicity:

#### Acute toxicity:

Identification		Concentration	Species	Genus
Xylene	LC50	>10 - 100 (96 h)		Fish
CAS: 1330-20-7	EC50	>10 - 100 (48 h)		Crustacear
EC: 215-535-7	EC50	>10 - 100 (72 h)		Algae
trizinc bis(orthophosphate)	LC50	>0.1 - 1 (96 h)		Fish
CAS: 7779-90-0	EC50	>0.1 - 1 (48 h)		Crustacear
EC: 231-944-3	EC50	>0.1 - 1 (72 h)		Algae
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacea
EC: 203-603-9	EC50	Non-applicable		
N-butyl acetate	LC50	Non-applicable		
CAS: 123-86-4	EC50	Non-applicable		
EC: 204-658-1	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacea
EC: 203-603-9	EC50	Non-applicable		
Ethylbenzene	LC50	42,3 mg/L (96 h)	Pimephales promelas	Fish
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacea
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
zinc oxide	LC50	0,82 mg/L (96 h)	Oncorhynchus kisutch	Fish
CAS: 1314-13-2	EC50	3,4 mg/L (48 h)	Daphnia magna	Crustacea
EC: 215-222-5	EC50	Non-applicable		
n-butyl acrylate	LC50	5,2 mg/L (96 h)	Salmo gairdneri	Fish
CAS: 141-32-2	EC50	230 mg/L (24 h)	Daphnia magna	Crustacea
EC: 205-480-7	EC50	5,5 mg/L (96 h)	Selenastrum capricornutum	Algae



# Date of compilation: 21/06/2022 Version: 1

# SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration	Species	Genus
Xylene	NOEC 1,3 mg/L	Oncorhynchus mykiss	Fish
CAS: 1330-20-7 EC: 215-535-7	NOEC 1,17 mg/L	Ceriodaphnia dubia	Crustacean
2-methoxy-1-methylethyl acetate	NOEC 47,5 mg/L	Oryzias latipes	Fish
CAS: 108-65-6 EC: 203-603-9	NOEC 100 mg/L	Daphnia magna	Crustacean
N-butyl acetate	NOEC Non-applicable		
CAS: 123-86-4 EC: 204-658-1	NOEC 23,2 mg/L	Daphnia magna	Crustacean
2-methoxy-1-methylethyl acetate	NOEC 47,5 mg/L	Oryzias latipes	Fish
CAS: 108-65-6 EC: 203-603-9	NOEC 100 mg/L	Daphnia magna	Crustacean
Ethylbenzene	NOEC Non-applicable		
CAS: 100-41-4 EC: 202-849-4	NOEC 0,96 mg/L	Ceriodaphnia dubia	Crustacean
zinc oxide	NOEC 0,44 mg/L	Oncorhynchus mykiss	Fish
CAS: 1314-13-2 EC: 215-222-5	NOEC 0,031 mg/L	Daphnia magna	Crustacean
n-butyl acrylate	NOEC Non-applicable		
CAS: 141-32-2 EC: 205-480-7	NOEC 0,136 mg/L	Daphnia magna	Crustacean

# 12.2 Persistence and degradability:

Identification	De	gradability	Biode	egradability
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
CAS: 108-65-6	COD	Non-applicable	Period	8 days
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
N-butyl acetate	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 123-86-4	COD	Non-applicable	Period	5 days
EC: 204-658-1	BOD5/COD	Non-applicable	% Biodegradable	84 %
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
CAS: 108-65-6	COD	Non-applicable	Period	8 days
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-41-4	COD	Non-applicable	Period	14 days
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %
n-butyl acrylate	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 141-32-2	COD	Non-applicable	Period	14 days
EC: 205-480-7	BOD5/COD	Non-applicable	% Biodegradable	61,3 %



# Date of compilation: 21/06/2022 Version: 1

# SECTION 12: ECOLOGICAL INFORMATION (continued)

# **12.3 Bioaccumulative potential:**

Identification	Bioaccur	nulation potential
Xylene	BCF	9
CAS: 1330-20-7	Pow Log	2.77
EC: 215-535-7	Potential	Low
2-methoxy-1-methylethyl acetate	BCF	1
CAS: 108-65-6	Pow Log	0.43
EC: 203-603-9	Potential	Low
N-butyl acetate	BCF	4
CAS: 123-86-4	Pow Log	1.78
EC: 204-658-1	Potential	Low
2-methoxy-1-methylethyl acetate	BCF	1
CAS: 108-65-6	Pow Log	0.43
EC: 203-603-9	Potential	Low
Ethylbenzene	BCF	1
CAS: 100-41-4	Pow Log	3.15
EC: 202-849-4	Potential	Low
n-butyl acrylate	BCF	37
CAS: 141-32-2	Pow Log	2.36
EC: 205-480-7	Potential	Moderate

## 12.4 Mobility in soil:

Identification	Absorp	tion/desorption		Volatility
Xylene	Кос	202	Henry	524,86 Pa·m <sup>3</sup> /mol
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes
N-butyl acetate	Кос	Non-applicable	Henry	Non-applicable
CAS: 123-86-4	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 204-658-1	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable
Ethylbenzene	Кос	520	Henry	798,44 Pa·m <sup>3</sup> /mol
CAS: 100-41-4	Conclusion	Moderate	Dry soil	Yes
EC: 202-849-4	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes
n-butyl acrylate	Кос	Non-applicable	Henry	Non-applicable
CAS: 141-32-2	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 205-480-7	Surface tension	2,598E-2 N/m (25 °C)	Moist soil	Non-applicable

# 12.5 Results of PBT and vPvB assessment:



#### Date of compilation: 21/06/2022 Version: 1

# SECTION 12: ECOLOGICAL INFORMATION (continued)

Product fails to meet PBT/vPvB criteria

**12.6 Endocrine disrupting properties:** 

Endocrine-disrupting properties: The product fails to meet the criteria.

### 12.7 Other adverse effects:

Not described

Profirs

# SECTION 13: DISPOSAL CONSIDERATIONS

#### **13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

#### Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable, HP4 Irritant — skin irritation and eye damage

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

# **Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

# SECTION 14: TRANSPORT INFORMATION

### Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

	14.1	UN number or ID number:	UN1263			
	14.2	UN proper shipping name:	PAINT			
	14.3	Transport hazard class(es):	3			
$\langle \simeq \rangle$		Labels:	3			
	14.4	Packing group:	III			
3	14.5	Environmental hazards:	No			
•	14.6	Special precautions for user				
		Special regulations:	163, 367, 650			
		Tunnel restriction code:	D/E			
		Physico-Chemical properties:	see section 9			
		Limited quantities:	5 L			
:	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable			
Transport of dar	igero	us goods by sea:				
With regard to IMDC 20 19:						

With regard to IMDG 39-18:



Date of c	ompilation: 2	1/06/2022	Version: 1						
SECT	ION 14: TR	ANSPORT 1	INFORMATION (continued)						
	3	14.1 14.2 14.3 14.4 14.5	UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user Special regulations: EmS Codes: Physico-Chemical properties: Limited quantities: Segregation group:	UN1263 PAINT 3 3 III No 223, 955, 163, 367 F-E, S-E see section 9 5 L Non-applicable					
		14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable					
	Transport	of dangero	us goods by air:						
	With regard	to IATA/ICA	NO 2022:						
	3	14.2 14.3 14.4 14.5	UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels: Packing group: Environmental hazards: Special precautions for user	UN1263 PAINT 3 3 III No					
			Physico-Chemical properties:	see section 9					
		14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable					
			INFORMATION	ation specific for the substance or	miytura	1			
15.1	••			on (EC) No 1907/2006 (REACH): Non-a					
			-						
		Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable							
		Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable							
	Article 95, REGULATION (EU) No 528/2012: Non-applicable								
	REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable								
	Seveso III:								
	Section		Description	1	Lower-tier requirements	Upper-tier requirements			

		requiremente	requiremente					
P5c	FLAMMABLE LIQUIDS	5000	50000					
Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):								

Shall not be used in:

-ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

# Other legislation:





# Date of compilation: 21/06/2022 Version: 1 SECTION 15: REGULATORY INFORMATION (continued) The product could be affected by sectorial legislation 15.2 Chemical safety assessment: The supplier has not carried out evaluation of chemical safety. SECTION 16: OTHER INFORMATION Legislation related to safety data sheets: The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878). Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: Non-applicable Texts of the legislative phrases mentioned in section 2: H315: Causes skin irritation. H412: Harmful to aquatic life with long lasting effects. H373: May cause damage to organs through prolonged or repeated exposure (Oral). H304: May be fatal if swallowed and enters airways. H226: Flammable liquid and vapour. H319: Causes serious eye irritation. Texts of the legislative phrases mentioned in section 3: The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 CLP Regulation (EC) No 1272/2008: Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled. Acute Tox. 4: H332 - Harmful if inhaled. Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Flam. Lig. 3: H226 - Flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1B: H317 - May cause an allergic skin reaction. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. **Classification procedure:** Skin Irrit. 2: Calculation method Aquatic Chronic 3: Calculation method STOT RE 2: Calculation method Asp. Tox. 1: Calculation method Flam. Liq. 3: Calculation method (2.6.4.3) Eye Irrit. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu Abbreviations and acronyms:



# Date of compilation: 21/06/2022 Version: 1

# SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.